

Key Features

• Speed: 260mm/sec

• Print width: 80mm

• Print head life: 150km

• Connectivity: USB + Serial + Lan

Printing	IHR-810
Printing Method	Direct Thermal
Printing Width	80mm
Resolution	203 dpi
Printing Speed	260 mm/s
Interface	USB+Serial+Lan / Bluetooth / WiFi Optional
Printing Paper	79.5±0.5mm x Ø80mm
Line Spacing	3.75mm (Adjustable by commands)
Printer Command	ESC/POS
Font	80mm paper : Font A - 42 columns or 48 columns/ Font B - 56 columns or 64 columns/
Character Size	ANK, Font A: 12x24 dots Font B: 9x17 dots

Barcode Character

1D Code UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE98

/CODE128

2D Code QR Code / PDF417

Buffer

Input Buffer128 kbNV Flash256 kb

Power

Power Adaptor AC: 100-240V, 50~60Hz Power Source Output: DC 24V/2.5A

Cash Drawer Output DC 24V/1A

Physical characteristics

Weight 1Kg

Dimensions (DxWxH) $190 \times 140 \times 135 \text{ mm}$

Enviromental Requirements

Work Environment Temperature (0~45°C), Humidity (10~80%) (Non-Condensing)

Storage Environment Temperature (-10~60°C), Humidity (10~90%)

Reliability

Auto Cutter Life 1.5 million cuts

Printer Head Life 150KM

Driver Win 9X / Win 2000 / Win 2003 / Win XP / Win 7 / Win 8 / Win 10 / Linux / MAC

